

## Oil Field Puller

*The Industry Leader*

### **Toughness the field demands.**

The **CM Oil Field Puller** can be used to pull, lift, drag or stretch. The rugged design is used in heavy-duty construction, industrial applications, or any tough outdoor service. The heavy duty jaw shackles make attaching large or multiple slings very simple and easy.

The features are:

- Capacities of 3/4 & 1 1/2 ton
- Tough aluminum alloy construction and powder coat finish
- Simple construction with fewer parts for ease of maintenance and lower inventories
- Hoistaloy hardened steel link type load chain for strength, long wear life and flexibility
- Weatherized Weston-type automatic braking system for positive load control
- Easy, one-hand operation and control — only 58 pounds of pull required for 3/4 ton model capacity
- Free wheeling for fast and easy attachment to load
- Optional zinc-plated chain available
- Lifetime warranty
- Metric rated
- Made in U.S.A.



#### Puller specifications

Rated capacity* (tons)	Product code	Standard† lift (ft.)	lift full loads (lbs.)	Min. distance between hooks (in)	Lever length (in.)	Reeving	Shackle opening (in.)	Approx. shipping weight (lbs)
3/4	4053	5	58	10 <sup>3</sup> / <sub>4</sub>	21 <sup>1</sup> / <sub>4</sub>	1	1.13	16
1 1/2	4055	5	89	14.25	21 <sup>1</sup> / <sub>4</sub>	1	1.25	26

† Can be supplied with lifts longer than 5 feet

**CM<sup>®</sup> HOISTS**  
*The Industry Leader*

Division of Columbus McKinnon Corporation  
140 JOHN JAMES AUDUBON PARKWAY  
AMHERST, NEW YORK 14228-1197  
800/888-0985 • 716/689-5400 • FAX: 716/689-5644  
www.cmhoists.com

#### \* **⚠ WARNING**

**Overloading and Improper Use Can Result in Injury**

**To Avoid Injury:**

- Do not exceed working load limit, load rating, or capacity.
- Do not use to lift people or loads near people.
- Use only alloy chain and attachments for overhead lifting.
- Read and follow all instructions.