

Products To Pull You Through The Tough Jobs

Lineman's Hoists Exclusive Features From The Reliable Leader

Get A Grip on Little Mule's Lineman's Strap Hoists. Little Mule offers multiple options for every application a linesman needs. These lightweight strap hoists are the "Linesman's Choice" in the utility industry.

- **Capacities** — Rated loads of 1000 and 1500 lbs. - single line; 2000 and 3000 lbs. - double line.
- **Handle Designed for Overload Protection** — Handle bends to warn of hazardous condition and prevents dangerous overload.
- **Hooks with Latches** — 360° swiveling hooks equipped with latches for positive load engagement.
- **Positive Load Holding in All Environments** — Double, interlocking pawl mechanism assures one pawl is engaged at all times.
- **Meets or Exceeds** — Minimum 4:1 design factor and all requirements of ASME/ANSI Standard B-30.21. All units tested at 125% of rated load.
- **Lightweight and Rugged** — Special cast aluminum and zinc alloy housings.
- **Corrosion Resistant** — All stainless steel springs and shafts.
- **Reduced Wear** — All rotating shafts are mounted on bronze bushings.
- **Self-Storing Web Drum** — Provides compact operation.
- **Easy Load Positioning** — Utilizes a double pawl system with multiple pawl stops for precise load adjustment.
- **Fast Strapping Take-Up** — Winding wheel provided for quick take-up or positioning of strap.
- **Open Construction** — Allows for easy cleaning and inspection.



S P E C I F I C A T I O N S

Single & Double Line Strap Hoist • 1000 - 3000 Lbs.

Model Number	SINGLE LINE			DOUBLE LINE			Web Strap Length (Ft.)	Handle Length (In.)	Ship Weight (Lbs.)
	Capacity (Lbs.)	Lift (Ft.)	Hook to Hook (Min.) (In.)	Capacity (Lbs.)	Lift (Ft.)	Hook to Hook (Min.) (in.)			
250A	1000	9	21	2000	4 ¹ / ₄	25	10	20	11 ¹ / ₂
300A	1500	9	21	3000	4 ¹ / ₄	25	10	20	11 ¹ / ₂
* 250DA	1000	9 ¹ / ₄	18	2000	4 ¹ / ₄	25	10	20	12
* 300DA	1500	9 ¹ / ₄	18	3000	4 ¹ / ₄	25	10	20	12
** 250CA	1000	9	21	2000	4 ¹ / ₄	25	10	20	11 ¹ / ₂
** 300CA	1500	9	21	3000	4 ¹ / ₄	25	10	20	11 ¹ / ₂
*** 250DHA	1000	9 ¹ / ₄	18	2000	4 ¹ / ₄	25	10	20	12
*** 300DHA	1500	9 ¹ / ₄	18	3000	4 ¹ / ₄	25	10	20	12

* Includes Hot Stick Rings on all Hooks, Control Surfaces and Quick Disconnect Shaft.

** Includes Swivel-Type Gate on All Hooks.

*** Includes Hot Stick-Type Gate Latch on all Hooks as well as Hot Stick rings on all Hooks, Control Surfaces and Quick Disconnect Shaft.

⚠ WARNING

Overloading and Improper Use Can Result In Injury

To Avoid Injury:

- Do not exceed working load limit, load rating, or capacity.
- Do not use to lift people or loads over people.
- Use only alloy chain and attachments for overhead lifting.
- Read and follow all instructions.

Country Club Road • PO Box 779
Wadesboro, NC 28170 USA

Phone: (800) 477-5003 (704) 694-2156

FAX: (800) 374-6853 (704) 694-6829

e-mail: coffing@cmworks.com

www.coffinghoists.com