

Model GT

Lever Tools For Long Distance Pulling Applications — Versatile

Engineered for Reliability & Versatility

- Rated loads from 1 to 3 tons, with standard wire rope length of 32 feet on 1 and 3 ton models; 65 feet on 2 ton model.
- Designed for heavy-duty pulling, rigging, dragging, stretching and lifting applications. Its versatility and ability suits this tool perfectly for use in the construction and transportation industries, as well as hundreds of other industrial applications.
- The large surface area of the dual clamping jaws provide an evenly distributed grip on the wire rope for smooth operation and low wear.
- Limitless wire rope travel provides versatility for use over long distances.
- The greater the force of the pull, the greater the clamping force of the jaws. Unique jaw design prevents damage to the wire rope.
- Easily replaceable shear pin design protects against dangerous overloads.



GT-1300-32



GT-2000-65



GT-3500-32

Easy to Operate

- Lightweight and compact design aides portability, yet built tough for long life and trouble-free service.
- Telescopic handle enhances portability and ease of operation.
- Periodic cleaning, inspection, and lubrication is all that is required for minimal maintenance.

SPECIFICATIONS

GT Wire Rope Lever Tool • 1 - 3 Ton

Model Number	Rated Capacity (Tons)	Product Code	Standard Wire Rope Length (Ft.)	Wire Rope Diam. (In.)	Lever Length Extended (In.)	Lever Length Retracted (In.)	Rope Advance † (In.)	Overall Dimensions (In.)	Net Weight* (Lbs.)	Net Weight** (Lbs.)
GT-1300-32	1	0013	32	5/16	29.1	21.3	1.30	19.7 x 9.1 x 4.0	35	18
GT-2000-65	2	0020	65	7/16	29.1	21.3	1.45	24.8 x 13.0 x 5.9	79	40
GT-3500-32	3	0035	32	5/8	29.1	21.3	0.78	28.6 x 12.8 x 7.0	94	66

† Per full stroke at rated load.

* Wire rope included

** Less wire rope.

Note: For complete dimensional data, refer to Little Mule Dimensional DataBook (LMDB-2).

⚠ WARNING

Overloading and Improper Use Can Result In Injury. See Warning on Back Cover.