

Model SLM

The Perfect Shop Hoist —
Easy to Use, H4 Duty

Easy to Use

- Small, compact design - commercial & industrial applications.
- Lightweight and portable. Easy installation and maintenance.
- H4 duty cycle (300 motor starts/hour).

Special Model Features

- Friction-type overload device prevents lifting excessive overloads.
- 10-pocket oblique lay liftwheel provides longer chain life and extended service.
- NEMA 4 industrial-rated pendant control.
- Lifetime, grease-lubricated gear train—less maintenance.
- Alloy load chain (zinc plated optional).
- Thermally protected motor prevents damage from possible overheating.
- D.C. braking system for positive load control.
- Durability — Epoxy powder-coat finish on rugged cast aluminum alloy frame.



250 - 1000 Lbs.
Made in USA

SPECIFICATIONS

SLM Electric Chain Hoist • 250 - 1000 Lbs.

Model Number	Capacity (Lbs.)	Number of Chains	Lifting Speeds (FPM)	Headroom (In.)	Housing Dimensions (In.)			Ship Wt. (Lbs.)
					H	W	L	
SLM-0216	250	1	16	11 1/6	4 1/16	5 15/16	12 1/2	28
SLM-0224	250	1	24	11 1/6	4 1/16	5 15/16	12 1/2	28
SLM-0240	250	1	40	11 1/6	4 1/16	5 15/16	12 1/2	28
SLM-0316	300	1	16	11 1/6	4 1/16	5 15/16	12 1/2	28
SLM-0324	300	1	24	11 1/6	4 1/16	5 15/16	12 1/2	28
SLM-0340	300	1	40	11 1/6	4 1/16	5 15/16	12 1/2	28
SLM-0508	500	2	8	11 1/6	4 1/16	5 15/16	12 1/2	34
SLM-0512	500	1	12	11 1/6	4 1/16	5 15/16	12 1/2	28
SLM-0516	500	1	16	11 1/6	4 1/16	5 15/16	12 1/2	28
SLM-0520	500	2	20	11 1/6	4 1/16	5 15/16	12 1/2	34
SLM-0524	500	1	24	11 1/6	4 1/16	5 15/16	12 1/2	28
SLM-0608	600	2	8	11 1/6	4 1/16	5 15/16	12 1/2	34
SLM-0612	600	2	12	11 1/6	4 1/16	5 15/16	12 1/2	34
SLM-0620	600	2	20	11 1/6	4 1/16	5 15/16	12 1/2	34
SLM-1006	1000	2	6	11 1/6	4 1/16	5 15/16	12 1/2	34
SLM-1008	1000	2	8	11 1/6	4 1/16	5 15/16	12 1/2	32
SLM-1012	1000	2	12	11 1/6	4 1/16	5 15/16	12 1/2	32

Note: Standard lifts 10 ft. Other lifts available. Standard push button drop is 4 ft. less than lift.

Voltagess - 115V - single phase (models available with contactor in PB station)
230V, 460V, 575V - 3-phase, 60 Hertz

Chain Containers: See page 14



The SLM is about 12" in length,
and weighs less than 35 lbs.

Note: For complete dimensional data,
refer to Little Mule Dimensional
DataBook (LMDB-2).