

MAV / MALV LONG HANDLE LEVER HOIST

Easy Operation, Heavy-Duty Construction

For heavy-duty pulling, stretching, or lifting in construction or industrial settings, the Coffing MAV / MALV Long Handle Lever Hoist is the ulitmate tool for everyday use.

Tough aluminum alloy construction and powder coat finish

Weatherproof for outdoor service

Simple construction with fewer parts for ease of maintenance and lower inventories

 Hoistaloy hardened steel link type load chain for strength, long wear life and flexibility

Weatherized Weston-type automatic braking system for positive load control

Easy, one-hand operation and control — only 58 pounds of pull required for 3/4 ton model capacity

Forged upper and lower hooks with latches standard

Free wheeling for fast and easy attachment to load

Upper and lower Latchlok hooks available for all capacities

Optional Load Limiter protection device stops transmission of lever forces protecting against dangerous overload

 Optional anchor sling simplifies attachment to allow anchor hook to swivel in tight space applications (3/4, 1 & 11/2 ton units only)

(800) 477-5003 • (704) 694-2156

email: coffing@cmworks.com

www.coffinghoists.com

FAX (800) 374-6853 • (704) 694-6829

Optional Load Sentry warns of overload condition

Optional zinc-plated chain available

Unlimited lift

Lifetime warranty Metric rated Made in U.S.A.

MAV / MALV Long Handle Lever Hoist 3/4 - 6 Ton Capacity 5 ft. Standard Lift

S P E C I F I C A T I O N S

| Capacity | | Product | Standard Lift* | Pull To Lift Full Loads | Minimum Dist. Between | Lever Length | Reeving | Hook Throat Openings | Approx. Shipping |
|----------|-------|---------|-------------------|----------------------------|--------------------------|-----------------|---------|-------------------------|---------------------|
| (lb.) | (Ton) | Code | (ft.) | (lb.) | Hooks (in.) | (in.) | | (in.) | Weight (lb.) |
| 1653 | 3/4 | 05401V | 5 | 58 | 10 3/4 | 21 1/4 | 1 | 1 1/32 | 16 |
| 2204 | 1 | 05437V | 5 | 80 | 14 1/4 | 21 1/4 | 1 | 1 1/8 | 26 |
| 3306 | 1 1/2 | 05408V | 5 | 89 | 14 1/4 | 21 1/4 | 1 | 1 1/8 | 26 |
| 6612 | 3 | 05411V | 5 | 95 | 16 15/16 | 21 1/4 | 2 | 1 7/32 | 38 |
| 13224 | 6 | 05417V | 5 | 96 | 21 3/8 | 21 1/4 | 4 | 1 3/4 | 73 |

* Standard lifts shown. Other lifts available - Consult factory

