



# Spacemaster® SX RX Program Hoists QUICK SHIP PROGRAM\*

www.rmhoist.com



## Standard Features

- Power supply 208/3/60, 230/3/60, 460/3/60 or 575/3/60
- Two speed hoist with a 6:1 speed ratio, contactor controlled
- Hoist motor is class F insulated, 60% effective duty and thermally protected
- Low maintenance, sealed hoist brake
- Trolley motion with inverter control (two-step multi speed or infinitely variable speed)
- Near true vertical lift (approximately 1/8" hook drift per foot of lift)
- Electro-mechanical load limit switch
- 4-position hoist limit switch
- IP55/NEMA 4 type control enclosure
- CSA c/us approved
- Trolley motor with compact disc brake
- Trolley bumpers
- Approximately 40:1 drum to rope diameter ratio for extended rope life

\* Per Leadtime Matrix





# RX Program Hoists

4501 Gateway Blvd.  
 Springfield, OH 45502  
 Phone: (937) 328-5100  
 Fax: (937) 325-5319  
 Nationwide Toll Free:  
 1-800-955-9967  
 www.rmhoist.com

**Bulletin No. RX-2015**

Spacemaster® is a registered trademark of R&M Materials Handling, Inc.

## RX Program Hoist Options:

115 Volt control transformer

Push button assembly pendant cable and manual reset hook operated limit switch

Patented track trolley wheels are optional on Normal Headroom models only

See SX price list for ControlMaster™ Aspire Hoist Inverter model options

Capacity	Model	Lift (ft.)	Lift Speed (fpm)	Reeving	Suspension Types
	SX2	39'-4", 62'-4"	40 / 6.6	2 P.S.	LO, NO
	SX2	39'-4", 62'-4"	20 / 3.1	2 P.S.	LO*, NO*
	SX3	39'-4", 62'-4"	40 / 6.6	2 P.S.	LO, NO
	SX3	39'-4", 62'-4"	50 / 7.8	2 P.S.	LO, NO
1 1/2 ton	SX2	19'-8", 31'-2"	20 / 3.1	4 P.S.	LO, NO
	SX3	39'-4", 62'-4"	40 / 6.6	2 P.S.	LO, NO
	SX3	39'-4", 62'-4"	50 / 7.8	2 P.S.	LO, NO
	SX2	19'-8", 31'-2"	20 / 3.1	4 P.S.	LO, NO
	SX4	39'-4", 59'-0"	40 / 6.6	2 P.S.	LO, NO, DO-55.12" Ga.
2 1/2 Ton	SX3	19'-8", 31'-2"	20 / 3.1	4 P.S.	LO, NO
	SX3	19'-8", 31'-2"	25 / 3.9	4 P.S.	LO, NO
	SX4	39'-4", 59'-0"	40 / 6.6	2 P.S.	LO, NO, DO-55.12" Ga.
3 Ton	SX3	19'-8", 31'-2"	20 / 3.1	4 P.S.	LO, NO
	SX3	19'-8", 31'-2"	25 / 3.9	4 P.S.	LO, NO
5 Ton	SX4	19'-8", 29'-6"	20 / 3.1	4 P.S.	LO, NO, DO-55.12" Ga.
	SX4	39'-4"	20 / 3.1	4 P.S.	LO
	SX5	59'-0"	40 / 6.6	2 P.S.	LO, NO, DO-55.12" Ga.
	SX5	78'-8"	40 / 6.6	2 P.S.	LO, DO-55.12" Ga.
	SX5	59'-0"	60 / 9.8	2 P.S.	LO**, NO**, DO**-55.12" Ga.
	SX5	78'-8"	60 / 9.8	2 P.S.	LO**, DO**-55.12" Ga.
7 1/2 Ton	SX5	29'-6"	20 / 3.1	4 P.S.	LO, NO, DO-55.12" Ga.
	SX5	39'-4"	20 / 3.1	4 P.S.	LO, DO-55.12" Ga.
	SX5	29'-6"	30 / 4.9	4 P.S.	LO**, NO**, DO**-55.12" Ga.
	SX5	39'-4"	30 / 4.9	4 P.S.	LO**, DO**-55.12" Ga.
10 Ton	SX5	29'-6"	20 / 3.1	4 P.S.	LO, NO, DO-55.12" Ga.
	SX5	39'-4"	20 / 3.1	4 P.S.	LO, DO-55.12" Ga.
	SX5	29'-6"	30 / 4.9	4 P.S.	LO**, NO**, DO**-55.12" Ga.
	SX5	39'-4"	30 / 4.9	4 P.S.	LO**, DO**-55.12" Ga.
15 Ton	SX5	32'-9"	13 / 2, 20 / 3.1	6 P.S.	DO**-78.74" Ga.
	SX5	26'-2"	10 / 1.5, 16 / 2.4	8 P.S.	DO**-78.74" Ga.
20 Ton	SX5	26'-2"	10 / 1.5, 16 / 2.4	8 P.S.	DO**-78.74" Ga.
	SX6	39'-4"	13 / 2	6 P.S.	DO**-78.74" Ga.

**Voltage exceptions:** \* 230v or 460v only, \*\* 460v or 575v only

R&M Materials Handling, Inc. may alter or amend the technical specifications identified herein at any time with or without notice.

© 2015, R&M Materials Handling, Inc.

R&M Materials Handling, Inc. is a proud member of the following organizations:

**YOUR DISTRIBUTOR CONTACT IS:**