

Wire rope lever hoists



Engineered for Reliable Operation

- Handle Designed for Overload Protection—Handle bends to warn of hazardous condition and prevent dangerous overload.
- Hooks with Hook Latches—360° swiveling hooks equipped with latches for positive load engagement.
- Meets ANSI Standard B30.21.
- Tested to 125% of Capacity.
- Made in U.S.A.

Portable and Durable

- Lightweight and Rugged—Special cast aluminum alloy housings.
- Heavy Duty Cable—Utilizes preformed and galvanized 7 x 19 (133 strand) extra flexible aircraft cable.
- Corrosion Resistant—All stainless steel springs and shafts.
- Reduced Wear—All rotating shafts are mounted on bronze bushings.

Easy to Operate

- Self-storing Cable Drum—Provides compact operation.
- Fast Cable Take-up—Winding wheel provided for quick take-up or positioning of cable.
- Easy Load Positioning—Utilizes a double interlocking pawl system for precise load adjustment.
- Positive Load Holding in All Environments—Provided by double interlocking pawl mechanism.
- Open Construction—Allows for easy cleaning and inspection.

Special Model Features

- All models are available with Bullard-type hooks.
- CM430CDPA equipped with oversized slip hooks— ideal for opening and closing boxcar doors.

*** ⚠ WARNING**

Overloading and improper use can result in injury.

To avoid injury:

- Do not exceed working load limit, load rating capacity
- Do not use to lift people or loads over people.
- use only alloy chain for overhead lifting.
- Read and follow all instructions.

Single & Double Line • 1000 - 4000 Lbs.

Specifications		SINGLE LINE			DOUBLE LINE			Cable Dia. x Length (In.) (Ft.)	Ship Weight (Lbs.)
		Capacity (Lbs.)	Lift (Ft.)	Hook to Hook (Min.) (In.)	Capacity (Lbs.)	Lift (Ft.)	Hook to Hook (Min.) (in.)		
04601W	115SA	1000	13 ³ / ₄	19	—	—	—	3/16 x 16	8 ³ / ₄
04602W	115DA	1000	13 ¹ / ₂	21	2000	6 ¹ / ₂	27	3/16 x 16	10 ¹ / ₂
04610W	505NA	1500	13	21	—	—	—	1/4 x 15	9 ¹ / ₂
04611W	202WNA	1500	12 ¹ / ₂	21	3000	6	27	1/4 x 15	11 ¹ / ₂
04620W	434WNA	1500	21 ¹ / ₂	22 ¹ / ₂	3000	10 ¹ / ₄	28 ¹ / ₂	1/4 x 24	13 ¹ / ₄
04621W	430CDPA	1500	21 ¹ / ₂	25	3000	10 ¹ / ₄	33 ¹ / ₂	1/4 x 24	16
04631W	404WNA	2000	12 ¹ / ₂	22 ¹ / ₂	4000	6	28 ¹ / ₂	9/32 x 15	13 ¹ / ₂