



GLOBAL KING™

EXPLOSION-PROOF OPTION

ELECTRIC WIRE ROPE HOISTS



C O L U M B U S M C K I N N O N C O R P O R A T I O N



GLOBAL KING™

ELECTRIC WIRE ROPE HOISTS



EXPLOSION-PROOF OPTION

The Yale Global King wire rope hoist is available with explosion-proof options featuring special enclosures, mc (metal clad) electrical cable and sealed fittings, intrinsically safe control stations and even Division 2 Hazardous Location motors if required.

Explosion-proof modifications are available on 5, 7½ and 10 metric ton Global King electric wire rope hoists with both underhung and top-running trolleys. These explosion-proof units are ideal for applications in Division 2, Class I, Group B, C & D hazardous environments where flammable gases, vapors and liquids are present.

Upon request, the Yale Global King explosion-proof unit is available with a tagged Division 2 Hazardous Location motor, which surpasses OSHA requirements.



DEFINITION OF DIVISION, CLASS & GROUP

DIVISION 2

Locations in which hazardous concentrations are handled, processed or used but are normally within closed containers or closed systems from which they can escape only in the case of accidental rupture or breakdown.

CLASS 1

Locations in which flammable gases or vapors are or may be present in the air in quantities sufficient to produce explosive or ignitable mixtures.

GROUP B

Atmospheres containing hydrogen, or gases and vapors of equivalent hazard, such as manufactured gas.

GROUP C

Atmospheres containing ethyl-ether vapors, ethylene or cyclo propane.

GROUP D

Atmospheres containing gasoline, hexane, naphtha, benzene, butane, alcohol, acetone, benzol, lacquer solvent vapors or natural gas.





KEY FEATURES DESIGNED TO MEET DIVISION 2, CLASS 1, GROUP B, C & D REQUIREMENTS:

- 1 NEMA 7/9 RATED CONTROL ENCLOSURE**
Hoist and trolley controls are housed in a NEMA 7/9 rated enclosure with hoist motion monitor, thermal overloads, over capacity limit switch and more. Two-speed control for smooth acceleration and precise load positioning.
- 2 MC (METAL CLAD) ELECTRICAL CABLE & FITTINGS**
Where required
- 3 STANDARD MOTOR**
Standard motor (not shown) is two-speed with a 4:1 ratio from high to low speed; giving a low speed for precise load handling and a high speed for fast throughput. Optional **Division 2 Hazardous Location motor** is shown in photo.
- 4 INTRINSICALLY SAFE LIMIT SWITCHES**
Standard upper/lower, geared control circuit hoist motion limit switch prevents lifting excessive overloads. Optional block operated upper control circuit limit switch is available.

INTRINSICALLY SAFE CONTROL STATION

Available when required (not shown).

STANDARD FEATURES:

WIRE ROPE DRUM

Machined from quality steel, deep-grooved with a rope guide to help ensure the rope stays in the grooves. Wire rope is secured to the drum with three heavy ductile iron clamps and designed to have three extra wraps of wire rope on the drum with the rope at full extension (low hook).

HEAVY DUTY DISC BRAKES

Rated at 200% torque, provides quick, positive stops and load holding.

WHEELS

Steel compound tread wheels for long life and use on either wide-flange or "S" beams. One wheel on each side of trolley driven for positive tracking.

GEARING

Triple reduction hoist gearing is oil bath lubricated, operating in an oil-tight, cast aluminum gear case.

FRAME

Heavy steel frame provides a solid foundation and positive alignment of key components.

TRUNNION-STYLE BLOCK & HOOK

Bearing mounted trunnion hook rotates 360° and swings back and forth 180° for easier load adjustment.

LOW HEADROOM

Reeved to a low-headroom design lower block for minimum headroom and maximum lift.

TROLLEY

Easily adjustable to handle a wide range of beam flange widths.



KNOW HOW...KNOW WHY

Columbus McKinnon is a global leader in providing expertise and training in the proper use and inspection of rigging and overhead lifting equipment. With a range of comprehensive programs and seminars conducted at venues throughout North America, as well as on site at private companies and industries, Columbus McKinnon courses include:

- Hoist Maintenance
- Load Securement
- Crane & Hoist Inspection
- Mobile Crane Operator
- Rigging
- Safe Hoisting
- Crane Operator Training
- Rigging Gear Inspection

Classes are available at our Niagara Training Center and the state-of-the-art **Hoist & Rigging Training Center of Excellence** in the Center for Occupational Health and Automobile Manufacturing (COHAM) lab at The Ohio State University. The COHAM lab is a hands-on learning center which allows attendees to understand how to properly use and inspect overhead lifting equipment. This leading edge training program is designed to increase workplace productivity and safety in a ergonomically friendly environment.



In addition to the strong knowledge base exemplified by comprehensive training programs, Columbus McKinnon is one of the only manufacturers supplying complete lifting systems to satisfy unique material handling requirements of users in a variety of environments. From jib cranes and hoists to chain slings, clamps, and related attachments; systems include products that are matched specifically to the lifting needs of the application. Products may also be modified in order to ensure that the proper system is in place for the job.

Whether your needs call for a single Global King wire rope hoist with explosion-proof features or a completely engineered system to outfit your production facility, Columbus McKinnon provides the products and expertise to keep your workforce productive and safe.



▲ WARNING

To Avoid Injury:

- Do not exceed working load limit, load rating, or capacity.
- Do not use to lift people or loads over people.
- Read and follow all instructions.



FAMILY OF BRANDS



Phone (800) 888.0985 • Fax: (716) 689.5644 • www.cmworks.com